



## Certificate of Analysis for 30mm Lug Caps

S.NO	Parameter	Std Specification
1.	Material Used	Electro Tin plate
2	Temper	DR-8
3.	Material Thickness	0.16mm $\pm$ 0.01mm
4.	Outside Diameter	33.6mm $\pm$ 0.2mm
5.	Inside Diameter	29.8mm $\pm$ 0.2mm
6	Lug to Lug Dia	28.3mm $\pm$ 0.2mm
7.	Number Of Lugs	3 nos of equal thickness
8.	Wt of cap with liner	3.5gm + 0.5gm
9.	Weight of liner	0.4 + 0.1gm
10	Cap Height	12.5 + 0.2mm
11	Vaccum	Satisfactory
12.	Laquer – external & internal	Should resist corrosion & scratch test (copper sulphate test)
13.	Lithography & colour	As per customer specs. & Shade card
14.	Scratches on print	Minor (<2%)
15.	Foreign deposit on pvc gasket/inside coating	Should be free from foreign deposit

- 1.) Sheets Used: Electrolytic Tinplate
- a.) Internally decorated with protective Decorative system to suit agreed Products and process conditions.
  - b.) Externally coated with designs and Colours varnished to protect dec.
- 2.) Sealing Gasket: FDA approved based sealing compound. The Gasket is sufficient tough to withstand the temperature process and thermal shocks during processing and yet have softness to give perfect seal when twisted by rollers of capping machine.

FOR ISSUED:

Q. C DEPTT: